

Some contributions to the simultaneous and indirect stabilization of multi-component systems

Louis Tebou

Florida International University
Miami

Workshop on Dynamics, Control and Numerics for Fractional PDEs
University of Puerto Rico at San Juan

December 5-7, 2018

Overview

- An abstract model

Overview

- An abstract model
- Simultaneous stabilization

Overview

- An abstract model
- Simultaneous stabilization
 - Brief literature

Overview

- An abstract model
- Simultaneous stabilization
 - Brief literature
 - Lamé systems with localized damping

Overview

- An abstract model
- Simultaneous stabilization
 - Brief literature
 - Lamé systems with localized damping
 - Euler-Bernoulli plate-wave system with localized damping

Overview

- An abstract model
- Simultaneous stabilization
 - Brief literature
 - Lamé systems with localized damping
 - Euler-Bernoulli plate-wave system with localized damping
 - Timoshenko beam with localized damping

Overview

- An abstract model
- Simultaneous stabilization
 - Brief literature
 - Lamé systems with localized damping
 - Euler-Bernoulli plate-wave system with localized damping
 - Timoshenko beam with localized damping
- Indirect stabilization

Overview

- An abstract model
- Simultaneous stabilization
 - Brief literature
 - Lamé systems with localized damping
 - Euler-Bernoulli plate-wave system with localized damping
 - Timoshenko beam with localized damping
- Indirect stabilization
 - Brief literature

Overview

- An abstract model
- Simultaneous stabilization
 - Brief literature
 - Lamé systems with localized damping
 - Euler-Bernoulli plate-wave system with localized damping
 - Timoshenko beam with localized damping
- Indirect stabilization
 - Brief literature
 - Kirchhoff plate-wave

Overview

- An abstract model
- Simultaneous stabilization
 - Brief literature
 - Lamé systems with localized damping
 - Euler-Bernoulli plate-wave system with localized damping
 - Timoshenko beam with localized damping
- Indirect stabilization
 - Brief literature
 - Kirchhoff plate-wave
 - Mindlin-Timoshenko plate

Overview

- An abstract model
- Simultaneous stabilization
 - Brief literature
 - Lamé systems with localized damping
 - Euler-Bernoulli plate-wave system with localized damping
 - Timoshenko beam with localized damping
- Indirect stabilization
 - Brief literature
 - Kirchhoff plate-wave
 - Mindlin-Timoshenko plate
- Some extensions and open problems

Model formulation

Let H and V be Hilbert spaces with $V \subset H$. Assume V is dense in H and the injection of V into H is compact. Denote by (\cdot, \cdot) the inner product in H , by $|\cdot|$ the corresponding norm, and by V' the dual of V . Consider the damped abstract equation

$$\begin{aligned} y_{tt} + Ay + By_t &= 0 \text{ in } (0, \infty) \\ y(0) = y^0 &\in V, \quad y_t(0) = y^1 \in H, \end{aligned}$$

where $A \in \mathcal{L}(V, V')$ is a selfadjoint coercive operator with $D(A^{\frac{1}{2}}) = V$, and $B \in \mathcal{L}(H)$ is a nonnegative operator.

Model formulation

Let H and V be Hilbert spaces with $V \subset H$. Assume V is dense in H and the injection of V into H is compact. Denote by (\cdot, \cdot) the inner product in H , by $|\cdot|$ the corresponding norm, and by V' the dual of V . Consider the damped abstract equation

$$\begin{aligned} y_{tt} + Ay + By_t &= 0 \text{ in } (0, \infty) \\ y(0) = y^0 &\in V, \quad y_t(0) = y^1 \in H, \end{aligned}$$

where $A \in \mathcal{L}(V, V')$ is a selfadjoint coercive operator with $D(A^{\frac{1}{2}}) = V$, and $B \in \mathcal{L}(H)$ is a nonnegative operator.

Introduce the energy

$$E(t) = \frac{1}{2} \{ |y_t(t)|^2 + |A^{\frac{1}{2}}y(t)|^2 \}, \quad \forall t \geq 0.$$

Theorem: Dafermos criterion

1970: Dafermos proves: the abstract system is strongly stable

$$\lim_{t \rightarrow \infty} E(t) = 0$$

if and only if

$$\text{Ker} B \cap \text{Ker}(A + \lambda I) = \{0\}, \quad \forall \lambda \in \mathbb{R}$$

where I denotes the identity operator on H .

Theorem: Dafermos criterion

1970: Dafermos proves: the abstract system is strongly stable

$$\lim_{t \rightarrow \infty} E(t) = 0$$

if and only if

$$\text{Ker} B \cap \text{Ker}(A + \lambda I) = \{0\}, \quad \forall \lambda \in \mathbb{R}$$

where I denotes the identity operator on H .

For the stabilization of single component systems, we refer to the contributions of Bardos-Lebeau-Rauch, Rauch-Taylor, Russell, Dafermos, Chen, Haraux, Komornik, Lasiecka, Nakao, Liu, Martinez, Triggiani, Zuazua,...

Brief literature

By simultaneous stabilization, we should understand stabilizing a multi-component system using the same damping mechanism in all components; the matrix defining the damping is degenerate.

Brief literature

By simultaneous stabilization, we should understand stabilizing a multi-component system using the same damping mechanism in all components; the matrix defining the damping is degenerate.

- 1986: Russell introduces the notion of simultaneous control for pdes when studying the boundary controllability of the Maxwell's equations.

Brief literature

By simultaneous stabilization, we should understand stabilizing a multi-component system using the same damping mechanism in all components; the matrix defining the damping is degenerate.

- 1986: Russell introduces the notion of simultaneous control for pdes when studying the boundary controllability of the Maxwell's equations.
- 1988: Lions (v.1, Controllability book) analyses simultaneous boundary control problems for two uncoupled waves, and for two uncoupled plates.

Brief literature

Consider the system of uncoupled wave equations

$$u_{jtt} - a_j \Delta u_j = 0 \text{ in } Q$$

$$u_j = 0 \text{ on } \Gamma \times (0, T)$$

$$u_j(x, 0) = u_j^0(x), \quad u_{jt}(x, 0) = u_j^1(x) \text{ in } \Omega, \quad j = 1, 2, \dots, q,$$

where $(u_j^0, u_j^1) \in H_0^1(\Omega) \times L^2(\Omega)$ for each j .

1988: Haraux (1988) shows for arbitrary nonempty open set ω :

- If $\sum_{j=1}^q u_j(x, t) = 0$ in $\omega \times (0, T)$ then $u_j^0 = 0, u_j^1 = 0$ in $\Omega, \forall j$.
provided that $a_j \neq a_k$ for all j, k with $j \neq k$.

- If $\sum_{j=1}^q u_j(x, t) = 0$ in $\omega \times (0, T)$ then $u_j^0 = 0, \quad u_j^1 = 0$ in $\Omega, \quad \forall j$.
provided that $a_j \neq a_k$ for all j, k with $j \neq k$.
- If $N = 1$ and T is large enough, or $\omega = \Omega$, then there exists $C > 0$:
for all j and all $(u_j^0, u_j^1) \in L^2(\Omega) \times H^{-1}(\Omega)$

$$\sum_{j=1}^q \{ \|u_j^0\|_{L^2(\Omega)}^2 + \|u_j^1\|_{H^{-1}(\Omega)}^2 \} \leq C \int_0^T \int_{\omega} \left| \sum_{j=1}^q u_j(x, t) \right|^2 dx dt$$

provided that $a_j \neq a_k$ for all j, k with $j \neq k$.

(GCC): Bardos-Lebeau-Rauch (1992): ω is an admissible control region in time T if every ray of geometric optics enters ω in a time less than T .

Theorem 1 (2012)

Let T_0 denote the best controllability time for a single wave equation with unit speed of propagation. Suppose that

$T > T_0 \max\{a_j^{-\frac{1}{2}}; j = 1, 2, \dots, q\}$ and (ω, T) satisfies (GCC). There exists a constant $C > 0$ such that for all $(u_j^0, u_j^1) \in H_0^1(\Omega) \times L^2(\Omega)$, $j = 1, 2, \dots, q$:

$$\sum_{j=1}^q \{ \|u_j^0\|_{H_0^1(\Omega)}^2 + \|u_j^1\|_{L^2(\Omega)}^2 \} \leq C \int_0^T \int_{\omega} \left| \sum_{j=1}^q u_{jt}(x, t) \right|^2 dx dt,$$

with $C = C(\Omega, \omega, T, (a_j)_j, q)$.

Lamé systems with localized damping

Given $(y_j^0, y_j^1)_j \in \left([H_0^1(\Omega)]^N \times [L^2(\Omega)]^N \right)^q$, and a function $d \in L^\infty(\Omega)$, $d \geq 0$, consider the damped elastodynamic system

$$y_{jtt} - \mu_j \Delta y_j - (\mu_j + \lambda_j) \nabla \operatorname{div}(y_j) + d \sum_{k=1}^q y_{kt} = 0 \text{ in } \Omega \times (0, \infty)$$

$$y_j = 0 \text{ on } \Gamma \times (0, \infty)$$

$$y_j(x, 0) = y_j^0(x), \quad y_{jt}(x, 0) = y_j^1(x), \text{ in } \Omega,$$

$$j = 1, 2, \dots, q,$$

where, for each j , μ_j and λ_j are the Lamé constants.

The total energy is given, for all $t \geq 0$, by

$$2E(t) = \sum_{j=1}^q \int_{\Omega} \{ |y_{jt}(x, t)|^2 + \mu_j |\nabla y_j(x, t)|^2 + (\mu_j + \lambda_j) |\operatorname{div}(y_j(x, t))|^2 \} dx$$

Lamé systems with localized damping

E is a nonincreasing function of the time variable as

$$\frac{dE}{dt} = - \int_{\Omega} d(x) \left| \sum_{k=1}^q y_{kt}(x, t) \right|^2 dx.$$

Lamé systems with localized damping

E is a nonincreasing function of the time variable as

$$\frac{dE}{dt} = - \int_{\Omega} d(x) \left| \sum_{k=1}^q y_{kt}(x, t) \right|^2 dx.$$

Question 1: Does the energy E decay to zero as time goes to infinity?

Lamé systems with localized damping

E is a nonincreasing function of the time variable as

$$\frac{dE}{dt} = - \int_{\Omega} d(x) \left| \sum_{k=1}^q y_{kt}(x, t) \right|^2 dx.$$

Question 1: Does the energy E decay to zero as time goes to infinity?

Question 2: Under which conditions is the Lamé system exponentially stable?

Lamé systems with localized damping

Theorem 2: Strong stability

Let ω be a nonempty subset of Ω . Suppose that d is positive in ω . The elastodynamic system is strongly stable:

$$\lim_{t \rightarrow \infty} E(t) = 0$$

if and only if the propagation speeds are pairwise distinct:

$$\mu_j \neq \mu_k \text{ and } \lambda_j + 2\mu_j \neq \lambda_k + 2\mu_k, \quad \forall j, k, j \neq k.$$

Lamé systems with localized damping

Theorem 2: Strong stability

Let ω be a nonempty subset of Ω . Suppose that d is positive in ω . The elastodynamic system is strongly stable:

$$\lim_{t \rightarrow \infty} E(t) = 0$$

if and only if the propagation speeds are pairwise distinct:

$$\mu_j \neq \mu_k \text{ and } \lambda_j + 2\mu_j \neq \lambda_k + 2\mu_k, \quad \forall j, k, j \neq k.$$

Proof method: Apply Dafermos criterion, or Benchimol or Arendt-Batty strong stability criterion, some linear algebra argument, and Imanuvilov-Yamamoto Carleman estimate.

A new unique continuation result

Let $T > 0$. Let ω be an arbitrary nonvoid open set contained in Ω . Consider the uncoupled elastodynamic system

$$\begin{aligned} y_{jtt} - \mu_j \Delta y_j - (\mu_j + \lambda_j) \nabla \operatorname{div}(y_j) &= 0 \text{ in } \Omega \times (0, T) \\ y_j &= 0 \text{ on } \Gamma \times (0, T) \\ j &= 1, 2, \dots, q. \end{aligned}$$

There exists $T_0 > 0$ such that for any $T > T_0$,

$$\sum_{j=1}^q y_{jt} = 0 \text{ in } \omega \times (0, T) \Rightarrow y_j = 0 \text{ in } \Omega \times (0, T), \quad \forall j$$

provided that

$$\mu_j \neq \mu_k \text{ and } \lambda_j + 2\mu_j \neq \lambda_k + 2\mu_k, \quad \forall j, k, j \neq k.$$

Lamé systems with localized damping

Theorem 3: Exponential stability

Let $(y_j^0, y_j^1)_j \in \left([H_0^1(\Omega)]^N \times [L^2(\Omega)]^N \right)^q$. Suppose

$$\mu_j \neq \mu_k, \quad \lambda_j + 2\mu_j \neq \lambda_k + 2\mu_k, \quad \text{and} \quad \lambda_j \mu_k = \lambda_k \mu_j, \quad \forall j, k, j \neq k.$$

Assume that ω satisfies the Liu geometric control condition, and suppose that the damping is effective in ω :

$$\exists d_0 > 0 : d(x) \geq d_0 \text{ a.e. } \omega.$$

There exist positive constants M and κ , independent of the initial data, such that the following energy decay estimate holds:

$$E(t) \leq M e^{-\kappa t} E(0), \text{ for all } t \geq 0.$$

Lamé systems with localized damping

Theorem 3: Exponential stability

Let $(y_j^0, y_j^1)_j \in \left([H_0^1(\Omega)]^N \times [L^2(\Omega)]^N \right)^q$. Suppose

$$\mu_j \neq \mu_k, \quad \lambda_j + 2\mu_j \neq \lambda_k + 2\mu_k, \quad \text{and} \quad \lambda_j \mu_k = \lambda_k \mu_j, \quad \forall j, k, j \neq k.$$

Assume that ω satisfies the Liu geometric control condition, and suppose that the damping is effective in ω :

$$\exists d_0 > 0 : d(x) \geq d_0 \text{ a.e. } \omega.$$

There exist positive constants M and κ , independent of the initial data, such that the following energy decay estimate holds:

$$E(t) \leq M e^{-\kappa t} E(0), \text{ for all } t \geq 0.$$

Proof method: FDM, multipliers technique, Huang or Prüss criterion.

An observability result

Let $T > 0$. Let ω be a nonempty open set in Ω satisfying the Liu geometric control condition. Consider the uncoupled elastodynamic system

$$\begin{aligned} y_{jtt} - \mu_j \Delta y_j - (\mu_j + \lambda_j) \nabla \operatorname{div}(y_j) &= 0 \text{ in } \Omega \times (0, T) \\ y_j &= 0 \text{ on } \Gamma \times (0, T) \\ y_j(x, 0) &= y_j^0(x), \quad y_{jt}(x, 0) = y_j^1(x), \text{ in } \Omega, \\ j &= 1, 2, \dots, q. \end{aligned}$$

There exists $T_0 > 0$ such that for any $T > T_0$, there exists $C > 0$:

$$E(0) \leq \int_0^T \int_{\omega} \left| \sum_{j=1}^q y_{jt}(x, t) \right|^2 dx dt,$$

provided that

$$\mu_j \neq \mu_k, \quad \lambda_j + 2\mu_j \neq \lambda_k + 2\mu_k, \quad \text{and} \quad \lambda_j \mu_k = \lambda_k \mu_j, \quad \forall j, k, j \neq k.$$

Euler-Bernoulli Plate-wave system

Consider the damped system

$$\left\{ \begin{array}{l} y_{tt} - \Delta y + d(x)(y_t + z_t) = 0 \text{ in } \Omega \times (0, \infty) \\ z_{tt} + \Delta^2 z + d(x)(y_t + z_t) = 0 \text{ in } \Omega \times (0, \infty) \\ y = 0, \quad z = 0, \quad \partial_\nu z = 0 \text{ on } \Gamma \times (0, \infty) \\ y(0) = y^0 \in H_0^1(\Omega), \quad y_t(0) = y^1 \in L^2(\Omega), \\ z(0) = z^0 \in H_0^2(\Omega), \quad z_t(0) = z^1 \in L^2(\Omega). \end{array} \right.$$

The total energy is given, for all $t \geq 0$, by

$$2E(t) = \int_{\Omega} \{|y_t(x, t)|^2 + |\nabla y(x, t)|^2 + |z_t(x, t)|^2 + |\Delta z(x, t)|^2\} dx,$$

Euler-Bernoulli Plate-wave system

E is a nonincreasing function of the time variable as

$$\frac{dE}{dt} = - \int_{\Omega} d(x) |y_t(x, t) + z_t(x, t)|^2 dx.$$

Euler-Bernoulli Plate-wave system

E is a nonincreasing function of the time variable as

$$\frac{dE}{dt} = - \int_{\Omega} d(x) |y_t(x, t) + z_t(x, t)|^2 dx.$$

Question 1: Does the energy E decay to zero as time goes to infinity?

Euler-Bernoulli Plate-wave system

E is a nonincreasing function of the time variable as

$$\frac{dE}{dt} = - \int_{\Omega} d(x) |y_t(x, t) + z_t(x, t)|^2 dx.$$

Question 1: Does the energy E decay to zero as time goes to infinity?

Question 2: Under which conditions is the system exponentially stable?

Euler-Bernoulli Plate-wave system

Theorem 4: Strong stability

Let ω be an arbitrary nonvoid open set contained in Ω . Suppose that the damping coefficient d is positive in ω .

The system is strongly stable:

$$\lim_{t \rightarrow \infty} E(t) = 0$$

provided that either $\text{meas}(\partial\omega \cap \partial\Omega) > 0$, or else, the only solution of $\Delta u = -u$ in Ω and $u = 0$ on $\partial\Omega$ is $u = 0$.

Another new unique continuation result

Let $T > 0$. Let ω be an arbitrary nonvoid open set contained in Ω . Consider the uncoupled system

$$\begin{cases} y_{tt} - \Delta y = 0 & \text{in } \Omega \times (0, T) \\ z_{tt} + \Delta^2 z = 0 & \text{in } \Omega \times (0, T) \\ y = 0, \quad z = 0, \quad \partial_\nu z = 0 & \text{on } \Gamma \times (0, T). \end{cases}$$

There exists $T_0 > 0$ such that for any $T > T_0$,

$$y_t + z_t = 0 \text{ in } \omega \times (0, T) \Rightarrow y = 0 \text{ and } z = 0 \text{ in } \Omega \times (0, T),$$

Another new unique continuation result

Let $T > 0$. Let ω be an arbitrary nonvoid open set contained in Ω . Consider the uncoupled system

$$\begin{cases} y_{tt} - \Delta y = 0 & \text{in } \Omega \times (0, T) \\ z_{tt} + \Delta^2 z = 0 & \text{in } \Omega \times (0, T) \\ y = 0, \quad z = 0, \quad \partial_\nu z = 0 & \text{on } \Gamma \times (0, T). \end{cases}$$

There exists $T_0 > 0$ such that for any $T > T_0$,

$$y_t + z_t = 0 \text{ in } \omega \times (0, T) \Rightarrow y = 0 \text{ and } z = 0 \text{ in } \Omega \times (0, T),$$

provided that $\text{meas}(\partial\omega \cap \partial\Omega) > 0$, or else, the only solution of $\Delta u = -u$ in Ω and $u = 0$ on $\partial\Omega$ is $u = 0$.

Euler-Bernoulli Plate-wave system

Theorem 5: Exponential stability

Let $(y^0, y^1) \in H_0^1(\Omega) \times L^2(\Omega)$ and $(z^0, z^1) \in H_0^2(\Omega) \times L^2(\Omega)$.

Assume that ω satisfies the Liu geometric control condition, and suppose that the damping is effective in ω :

$$\exists d_0 > 0 : d(x) \geq d_0 \text{ a.e. } \omega.$$

There exist positive constants M and κ , independent of the initial data, such that the following energy decay estimate holds:

$$E(t) \leq Me^{-\kappa t} E(0), \text{ for all } t \geq 0.$$

An observability inequality

Let $T > 0$. Let ω be a nonempty open set in Ω satisfying the Liu geometric control condition.

Consider the uncoupled system

$$\begin{cases} y_{tt} - \Delta y = 0 & \text{in } \Omega \times (0, T) \\ z_{tt} + \Delta^2 z = 0 & \text{in } \Omega \times (0, T) \\ y = 0, \quad z = 0, \quad \partial_\nu z = 0 & \text{on } \Gamma \times (0, T). \end{cases}$$

There exists $T_0 > 0$ such that for any $T > T_0$, there exists $C > 0$:

$$E(0) \leq \int_0^T \int_\omega |y_t(x, t) + z_t(x, t)|^2 dx dt,$$

Timoshenko beam

Let $L > 0$, and set $\Omega = (0, L)$, and $\omega = (l_1, l_2)$ with $0 \leq l_1 < l_2 \leq L$. Consider the damped Timoshenko system:

$$\begin{cases} \rho_1 y_{tt} - k(y_x + z)_x + a(x)(y_t + z_t) = 0 & \text{in } (0, L) \times (0, \infty) \\ \rho_2 z_{tt} - \sigma z_{xx} + k(y_x + z) + a(x)(y_t + z_t) = 0 & \text{in } (0, L) \times (0, \infty), \end{cases}$$

with the boundary conditions:

$$\text{(DD)} \quad y(0, t) = 0, \quad y(L, t) = 0, \quad z(0, t) = 0, \quad z(L, t) = 0, \text{ or else}$$

$$\text{(DN)} \quad y(0, t) = 0, \quad y(L, t) = 0, \quad z_x(0, t) = 0, \quad z_x(L, t) = 0, \quad t > 0$$

and the initial conditions:

$$y(x, 0) = y^0(x), \quad y_t(x, 0) = y^1(x), \quad z(x, 0) = z^0(x), \quad z_t(x, 0) = z^1(x),$$

Timoshenko beam

Let $L > 0$, and set $\Omega = (0, L)$, and $\omega = (l_1, l_2)$ with $0 \leq l_1 < l_2 \leq L$. Consider the damped Timoshenko system:

$$\begin{cases} \rho_1 y_{tt} - k(y_x + z)_x + a(x)(y_t + z_t) = 0 & \text{in } (0, L) \times (0, \infty) \\ \rho_2 z_{tt} - \sigma z_{xx} + k(y_x + z) + a(x)(y_t + z_t) = 0 & \text{in } (0, L) \times (0, \infty), \end{cases}$$

with the boundary conditions:

(DD) $y(0, t) = 0, \quad y(L, t) = 0, \quad z(0, t) = 0, \quad z(L, t) = 0$, or else

(DN) $y(0, t) = 0, \quad y(L, t) = 0, \quad z_x(0, t) = 0, \quad z_x(L, t) = 0, \quad t > 0$

and the initial conditions:

$y(x, 0) = y^0(x), \quad y_t(x, 0) = y^1(x), \quad z(x, 0) = z^0(x), \quad z_t(x, 0) = z^1(x),$

The damping coefficient a is a nonnegative bounded measurable function, which is positive in ω only.

The energy and main questions

Introduce the energy

$$E(t) = \frac{1}{2} \int_{\Omega} \{ \rho_1 |y_t(x, t)|^2 + k |y_x(x, t) + z(x, t)|^2 \} dx \\ + \frac{1}{2} \int_{\Omega} \{ \rho_2 |z_t(x, t)|^2 + \sigma |z_x(x, t)|^2 \} dx, \quad \forall t \geq 0.$$

The energy E is a nonincreasing function of the time variable t as we have for every $t \geq 0$, (hereafter, $'$ denotes differentiation with respect to time)

$$E'(t) = - \int_{\Omega} a(x) |y_t(x, t) + z_t(x, t)|^2 dx.$$

The energy and main questions

Introduce the energy

$$E(t) = \frac{1}{2} \int_{\Omega} \{ \rho_1 |y_t(x, t)|^2 + k |y_x(x, t) + z(x, t)|^2 \} dx \\ + \frac{1}{2} \int_{\Omega} \{ \rho_2 |z_t(x, t)|^2 + \sigma |z_x(x, t)|^2 \} dx, \quad \forall t \geq 0.$$

The energy E is a nonincreasing function of the time variable t as we have for every $t \geq 0$, (hereafter, $'$ denotes differentiation with respect to time)

$$E'(t) = - \int_{\Omega} a(x) |y_t(x, t) + z_t(x, t)|^2 dx.$$

As before, our main purpose is to answer the following questions:

- Does the energy $E(t)$ decay to zero as the time variable t goes to infinity?
- If so, how fast? And if not, why?

Timoshenko beam

Theorem 6: Strong stability

Suppose that ω is an arbitrary nonempty open interval in Ω . Let the damping coefficient a be positive in ω . In either of the **(DD)** or **(DN)** case, the associated system is strongly stable:

$$\lim_{t \rightarrow \infty} E(t) = 0$$

if and only if $\partial\omega \cap \partial\Omega \neq \emptyset$.

Timoshenko beam

Theorem 7: Exponential stability

Suppose that ω is an arbitrary nonempty open interval in Ω with $\partial\omega \cap \partial\Omega \neq \emptyset$. Let the damping coefficient a satisfy

$$a(x) \geq a_0 > 0, \text{ a.e. in } \omega.$$

There exist positive constants M and κ , independent of the initial data, such that the following energy decay estimate holds:

$$E(t) \leq Me^{-\kappa t} E(0), \text{ for all } t \geq 0.$$

Brief literature

Notion explicitly introduced by Russell (1993), involves a coupled system of second order evolution equations where the damping occurs in one component of the system only.

Brief literature

Notion explicitly introduced by Russell (1993), involves a coupled system of second order evolution equations where the damping occurs in one component of the system only.

We can broaden the notion to account for thermoelasticity or fluid-structure models where the dissipation is induced by the heat or parabolic component only.

Other contributors include Dafermos, Lasiecka and collaborators, Burns and collaborators, Lebeau-Zuazua, Perla Menzala-Zuazua, Rauch-Zhang-Zuazua, Triggiani-Avalos, Zhang-Zuazua, Alabau, Alabau-Cannarsa-Komornik,...

Mindlin-Timoshenko plate

$$\rho_1 y_{tt} - k \operatorname{div}(\nabla y + z) = 0 \text{ in } \Omega \times (0, \infty)$$

$$\rho_2 z_{tt} - \mu \Delta z - (\lambda + \mu) \nabla \operatorname{div} z + k(\nabla y + z) + az_t = 0 \text{ in } \Omega \times (0, \infty)$$

$$y = 0, \quad z = 0 \text{ on } \partial\Omega \times (0, \infty)$$

$$y(\cdot, 0) = y^0 \in H_0^1(\Omega), \quad y_t(\cdot, 0) = y^1 \in L^2(\Omega),$$

$$z(\cdot, 0) = z^0 \in [H_0^1(\Omega)]^N, \quad z_t(\cdot, 0) = z^1 \in [L^2(\Omega)]^N.$$

Mindlin-Timoshenko plate

$$\begin{aligned} \rho_1 y_{tt} - k \operatorname{div}(\nabla y + z) &= 0 \text{ in } \Omega \times (0, \infty) \\ \rho_2 z_{tt} - \mu \Delta z - (\lambda + \mu) \nabla \operatorname{div} z + k(\nabla y + z) + az_t &= 0 \text{ in } \Omega \times (0, \infty) \\ y = 0, \quad z = 0 &\text{ on } \partial\Omega \times (0, \infty) \\ y(\cdot, 0) = y^0 \in H_0^1(\Omega), \quad y_t(\cdot, 0) = y^1 \in L^2(\Omega), \\ z(\cdot, 0) = z^0 \in [H_0^1(\Omega)]^N, \quad z_t(\cdot, 0) = z^1 \in [L^2(\Omega)]^N. \end{aligned}$$

In the one-dimensional setting, the system, known as the Timoshenko beam equations, describes the motion of a beam when the effects of rotatory inertia are accounted for; the transverse displacement is represented by y while z denotes the shear angle displacement.

In 2D, that system is known as the Mindlin-Timoshenko plate equations, where y represents the vertical deflection and z stands for the rotation angles of a filament.

In 2D, that system is known as the Mindlin-Timoshenko plate equations, where y represents the vertical deflection and z stands for the rotation angles of a filament.

The constants ρ_1 , ρ_2 , k , and μ are physical constants and are all positive. In particular, the constants λ and μ are the Lamé constants with $\lambda + \mu > 0$.

Mindlin-Timoshenko plate

2009: Fernández-Sare shows that the system is polynomially stable.

Mindlin-Timoshenko plate

2009: Fernández-Sare shows that the system is polynomially stable.

2011: Nicaise generalizes and improves Fernandez-Sare result to account for anisotropic cases, but still, only polynomial stability is established.

Mindlin-Timoshenko plate

2009: Fernández-Sare shows that the system is polynomially stable.

2011: Nicaise generalizes and improves Fernandez-Sare result to account for anisotropic cases, but still, only polynomial stability is established.

It is well-known that the indirectly damped Timoshenko beam, ($N = 1$), is exponentially stable if and only if

$$(*) \quad \frac{k}{\rho_1} = \frac{2\mu + \lambda}{\rho_2}.$$

Mindlin-Timoshenko plate

2009: Fernández-Sare shows that the system is polynomially stable.

2011: Nicaise generalizes and improves Fernandez-Sare result to account for anisotropic cases, but still, only polynomial stability is established.

It is well-known that the indirectly damped Timoshenko beam, ($N = 1$), is exponentially stable if and only if

$$(*) \quad \frac{k}{\rho_1} = \frac{2\mu + \lambda}{\rho_2}.$$

Questions: Is the Mindlin-Timoshenko system exponentially stable under $(*)$?

Mindlin-Timoshenko plate

2009: Fernández-Sare shows that the system is polynomially stable.

2011: Nicaise generalizes and improves Fernandez-Sare result to account for anisotropic cases, but still, only polynomial stability is established.

It is well-known that the indirectly damped Timoshenko beam, ($N = 1$), is exponentially stable if and only if

$$(*) \quad \frac{k}{\rho_1} = \frac{2\mu + \lambda}{\rho_2}.$$

Questions: Is the Mindlin-Timoshenko system exponentially stable under $(*)$? **What happens when $(*)$ fails?**

Energy estimates

Introduce the energy

$$E(t) = \frac{1}{2} \int_{\Omega} \{\rho_1 |y_t(x, t)|^2 + k |\nabla y(x, t) + z(x, t)|^2\} dx \\ + \frac{1}{2} \int_{\Omega} \{\rho_2 |z_t(x, t)|^2 + \mu |\nabla z(x, t)|^2 + (\lambda + \mu) |\operatorname{div} z(x, t)|^2\} dx, \quad \forall t \geq 0$$

Let ω satisfy Liu geometric constraint. Suppose that the damping coefficient a further satisfies

$$\exists a_0 > 0 : a(x) \geq a_0, \text{ a.e. } \omega.$$

Energy estimates

- If (*) holds, then the energy decays exponentially:

$$\exists M > 0, \exists \zeta > 0 : E(t) \leq Me^{-\zeta t} E(0), \quad \forall t \geq 0.$$

- If (*) fails, then the energy decays polynomially:

$$\exists M = M(\text{initial data}) > 0, \exists \zeta > 0 : E(t) \leq \frac{M}{(1+t)},$$

provided

$$(y^0, y^1) \in (H^2(\Omega) \cap H_0^1(\Omega)) \times H_0^1(\Omega)$$

and

$$(z^0, z^1) \in [(H^2(\Omega) \cap H_0^1(\Omega))]^N \times [H_0^1(\Omega)]^N.$$

Kirchhoff plate-wave

Joint work with Ahmed Hajej (U. Cergy-Pontoise, France) and Zayd Hajjej (U. Gabes, Tunisia)

Undamped Kirchhoff plate/ damped wave

Consider the following weakly coupled system of Kirchhoff plate and wave equations:

$$\left\{ \begin{array}{ll}
 u_{tt} - \gamma \Delta u_{tt} + \Delta^2 u + \alpha v = 0 & \text{in } \Omega \times (0, \infty) \\
 v_{tt} - \Delta v + v_t + \alpha u = 0 & \text{in } \Omega \times (0, \infty) \\
 u = \partial_\nu u = 0 & \text{on } \Gamma_0 \times (0, \infty) \\
 \Delta u + (1 - \mu) B_1 u = 0 & \text{on } \Gamma_0 \times (0, \infty) \\
 \partial_\nu \Delta u - \gamma \partial_\nu u_{tt} + (1 - \mu) B_2 u = 0 & \text{on } \Gamma_1 \times (0, \infty) \\
 v = 0 & \text{on } \Gamma \times (0, \infty) \\
 u(0) = u^0 \in V, \quad u_t(0) = u^1 \in H_0^1(\Omega), \\
 v(0) = v^0 \in H_0^1(\Omega), \quad v_t(0) = v^1 \in L^2(\Omega).
 \end{array} \right.$$

Undamped Kirchhoff plate/ damped wave

Ω is an open set of \mathbb{R}^2 with regular boundary $\Gamma = \partial\Omega = \Gamma_0 \cup \Gamma_1$ such that $\bar{\Gamma}_0 \cap \bar{\Gamma}_1 = \emptyset$,

The constant $\gamma > 0$ is the rotational inertia of the plate and the constant $0 < \mu < \frac{1}{2}$ is the Poisson coefficient.

The boundary operators B_1, B_2 are defined by

$$B_1 u = 2\nu_1\nu_2 u_{xy} - \nu_1^2 u_{yy} - \nu_2^2 u_{xx},$$

$$B_2 u = \partial_\tau \left((\nu_1^2 - \nu_2^2) u_{xy} + \nu_1\nu_2 (u_{yy} - u_{xx}) \right),$$

where $\nu = (\nu_1, \nu_2)$ is the unit outer normal vector to Γ and $\tau = (-\nu_2, \nu_1)$ is a unit tangent vector.

Energy estimates.

Introduce the energy, (setting $P_\gamma u = u - \gamma \Delta u$)

$$E(t) = \frac{1}{2} \int_{\Omega} \{ |P_\gamma^{\frac{1}{2}} u_t|^2 + |\Delta u|^2 + |v_t|^2 + |\nabla v|^2 + 2\alpha uv \} (x, t) dx.$$

We have:

$$E(t) \leq \frac{C_\alpha}{(t+1)^{\frac{1}{3}}} \left(\|u^0\|_{H^3(\Omega)}^2 + \|u^1\|_{H^2(\Omega)}^2 + \|v^0\|_{H^2(\Omega)}^2 + \|v^1\|_{H_0^1(\Omega)}^2 \right).$$

FDM, interpolation, good choice of functional inequalities,
Borichev-Tomilov criterion.

Damped Kirchhoff plate/ undamped wave

$$\left\{ \begin{array}{ll}
 u_{tt} - \gamma \Delta u_{tt} + \Delta^2 u + \alpha v + u_t = 0 & \text{in } \Omega \times (0, \infty) \\
 v_{tt} - \Delta v + \alpha u = 0 & \text{in } \Omega \times (0, \infty) \\
 u = \partial_\nu u = 0 & \text{on } \Gamma_0 \times (0, \infty) \\
 \Delta u + (1 - \mu) B_1 u = 0 & \text{on } \Gamma_0 \times (0, \infty) \\
 \partial_\nu \Delta u - \gamma \partial_\nu u_{tt} + (1 - \mu) B_2 u = 0 & \text{on } \Gamma_1 \times (0, \infty) \\
 v = 0 & \text{on } \Gamma \times (0, \infty) \\
 u(0) = u^0 \in V, \quad u_t(0) = u^1 \in H_0^1(\Omega), \\
 v(0) = v^0 \in H_0^1(\Omega), \quad v_t(0) = v^1 \in L^2(\Omega).
 \end{array} \right.$$

Energy estimates.

Introduce the energy

$$E(t) = \frac{1}{2} \int_{\Omega} \{ |p_{\gamma} u_t|^2 + |\Delta u|^2 + |v_t|^2 + |\nabla v|^2 + 2\alpha uv \} (x, t) dx.$$

We have:

$$E(t) \leq \frac{C_{\alpha}}{(t+1)^{\frac{1}{4}}} \left(\|u^0\|_{H^3(\Omega)}^2 + \|u^1\|_{H^2(\Omega)}^2 + \|v^0\|_{H^2(\Omega)}^2 + \|v^1\|_{H_0^1(\Omega)}^2 \right).$$

- ① Obtaining logarithmic energy decay estimates in the case of simultaneous stabilization in the multidimensional setting when ω is an arbitrary nonempty open subset of Ω .

- 1 Obtaining logarithmic energy decay estimates in the case of simultaneous stabilization in the multidimensional setting when ω is an arbitrary nonempty open subset of Ω .
- 2 What about the case of indefinite damping mechanism?

- 1 Obtaining logarithmic energy decay estimates in the case of simultaneous stabilization in the multidimensional setting when ω is an arbitrary nonempty open subset of Ω .
- 2 What about the case of indefinite damping mechanism?
- 3 The case of nonlinear multi-component systems is also open.

- 1 Obtaining logarithmic energy decay estimates in the case of simultaneous stabilization in the multidimensional setting when ω is an arbitrary nonempty open subset of Ω .
- 2 What about the case of indefinite damping mechanism?
- 3 The case of nonlinear multi-component systems is also open.
- 4 The fractional versions of those problems are widely open.

- 1 Obtaining logarithmic energy decay estimates in the case of simultaneous stabilization in the multidimensional setting when ω is an arbitrary nonempty open subset of Ω .
- 2 What about the case of indefinite damping mechanism?
- 3 The case of nonlinear multi-component systems is also open.
- 4 The fractional versions of those problems are widely open.

And if anyone thinks that he knows anything, he knows nothing yet as he ought to know.

THANKS!